


7.3 HZ Aseptic Nozzle

acc. DIN 11864 - 1


Design

- Material: 1.4404 or 1.4435, (1.4462, 2.4602, etc. (on request))
- DN: from 10 to 100
- h: against customers requirements (standard h = 40 mm)
- conical shaped
- Heavy wall, on demand (standard t = 4 mm)
- Surface: machined $Ra < 1,2 \mu m$

Threated nozzle without gasket groove



Grooved nozzle




7.3 HZ Aseptic Nozzle

acc. DIN 11864 - 2


Design

- Material: 1.4404 or 1.4435, (1.4462, 2.4602, etc. (on request))
- DN: from 10 to 100
- h: against customers requirements (standard h = 40 mm)
- conical shaped
- Heavy wall, on demand (standard t = 4 mm)
- Surface: machined $Ra < 1,2 \mu m$

Nozzle without gasket groove



Grooved nozzle



zimmerlin
EDELSTAHL-TECHNIK



Zimmerlin GmbH
Edelstahl-Technik
Frohmattenstr. 19
D-79268 Bötzingen

Tel. +49(0)7663-6088-0
Fax +49(0)7663-6088-88
info@zimmerlin.de
www.zimmerlin.de




Stand: Juni 2015


Design

- Material: 1.4404 or 1.4435, (1.4462, 2.4602, etc. (on request))
- DN: from 10 to 100
- h: against customers requirements (standard h = 40 mm)
- conical shaped
- Heavy wall, on demand (standard t = 4 mm)
- Surface: machined $Ra < 1,2 \mu m$

Threated nozzle without gasket groove



Grooved nozzle




HZ Aseptic Flange 7.3

PAD-flange


Design

- Material: 1.4404 or 1.4435, (1.4462, 2.4602, etc. (on request))
- DN: from 50 to 200
- h: on demand (standard h=25mm)
- Surface: machined $Ra < 1,2 \mu m$

Flange without gasket groove



Flange with gasket groove



Stand: Juni 2015

Tel. +49(0)7663-6088-0
Fax +49(0)7663-6088-88
info@zimmerlin.de
www.zimmerlin.de

Zimmerlin GmbH
Edelstahl-Technik
Frohmattenstr. 19
D-79268 Bötzingen

