



ARCHON

www.ARCHONind.com





No:		NW:		Material (wetted):					
Gasket:		<input type="checkbox"/> with FDA		Press.:	psi	Temp.:	°F	<input type="checkbox"/> PED	<input type="checkbox"/> ASME
Neck length		in	thickness:	in.	Lid thickness:		in.	<input type="checkbox"/> Pharma flanges	
<input type="checkbox"/> with spring assist				<input type="checkbox"/> with locking pin					
<input type="checkbox"/> with safety grill				with safety cross		<input type="checkbox"/>			
Eye bolts with:		<input type="checkbox"/> plastic handles		<input type="checkbox"/> stainless steel		<input type="checkbox"/> others:			
Hinge:		<input type="checkbox"/> foldable		<input type="checkbox"/> swiveling (side)		<input type="checkbox"/> without hinge		<input type="checkbox"/> for side installation	
Surface:		<input type="checkbox"/> pickled		<input type="checkbox"/> grinded inside:		Neck Ra <		μm , Cover Ra <	
		<input type="checkbox"/> blasted		<input type="checkbox"/> grinded outside:		Neck Ra <		μm , Cover Ra <	
X-Ray examination:		<input type="checkbox"/> Neck		%		<input type="checkbox"/> Cover		%	
								<input type="checkbox"/> with MTR	
Others (e.g. Nozzles, other Documents...):									